

Job 25080283B	Truss S30	Truss Type SCISSORS	Qty 16	Ply 1	Westwood C.C. 400733-012 Job Reference (optional)	Attachment 08		
UFP Site Built, LLC, UFP 20/20			Run: 8.830 s Apr 11 2025 Print: 8.830 s Apr 11 2025 MiTek Industries, Inc. Wed Aug 6 12:07:12 2025 Page 1 ID:ZHBB8ESp8faLeAkcyUvt6226yE-IE1k8ocvcdHAgb_3Opyej6VfZmJueKeLKhW0Yqb?D					
0-10-8 0-10-8	6-3-10 6-3-10	10-11-10 4-8-0	15-0-0 4-0-6	19-0-6 4-0-6	23-8-6 4-8-0	30-0-0 6-3-10	30-10-8 0-10-8	
Scale = 1:52.6								
8-8-0 8-8-0		15-0-0 6-4-0		21-4-0 6-4-0		30-0-0 8-8-0		
Plate Offsets (X, Y)-- [13:0-6-0,0-5-0]								
LOADING (psf) TCLL 30.0 TCDL 5.0 BCLL 0.0 BCDL 5.0	SPACING- Plate Grip DOL 1.15 Lumber DOL 1.15 Rep Stress Incr NO Code IBC2021/TPI2014	CSI. TC 0.80 BC 0.78 WB 0.78 Matrix-MS	DEFL. Vert(LL) -0.90 13-14 >399 Vert(CT) -1.17 13-14 >307 Horz(CT) 0.57 10 n/a	in (loc) 13-14 13-14 10	l/defl 240 180 n/a	L/d 240 180 n/a	PLATES MT20 M18AHS Weight: 177 lb	GRIP 197/144 142/136 FT = 20%
LUMBER- TOP CHORD 2x6 SP No.1 *Except* T1: 2x6 SP 2400F 2.0E BOT CHORD 2x6 SP 2400F 2.0E WEBS 2x4 SPF No.2 *Except* W4: 2x6 SP No.1				BRACING- TOP CHORD 2-0-0 oc purlins (2-6-10 max.). BOT CHORD Rigid ceiling directly applied or 5-8-14 oc bracing.				
REACTIONS. (lb/size) 2=2716/0-8-8, 10=2716/0-8-8 Max Horz 2=175(LC 15) Max Uplift2=764(LC 10), 10=764(LC 11)								
FORCES. (lb) - Maximum Compression/Maximum Tension TOP CHORD 1-2=0/32, 2-21=-10937/3569, 3-21=-10790/3577, 3-22=-10088/3233, 4-22=-10027/3246, 4-5=-7905/2580, 5-6=-7800/2590, 6-7=-7800/2590, 7-8=-7905/2580, 8-23=-10027/3246, 9-23=-10088/3233, 9-24=-10790/3577, 10-24=-10937/3569, 10-11=0/32 BOT CHORD 2-14=-3268/10380, 13-14=-2795/9241, 12-13=-2795/9241, 10-12=-3268/10380 WEBS 6-13=-1333/4353, 3-14=-872/482, 4-14=-149/728, 4-13=-2429/741, 8-13=-2429/748, 8-12=-162/728, 9-12=-872/497								
NOTES. 1) Unbalanced roof live loads have been considered for this design. 2) Wind: ASCE 7-16: Vult=115mph (3-second gust) Vasd=91mph; TCDL=3.0psf; BCDL=3.0psf; h=20ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-7-13 to 3-4-3, Interior(1) 3-4-3 to 10-11-10, Exterior(2R) 10-11-10 to 19-0-6, Interior(1) 19-0-6 to 26-7-13, Exterior(2E) 26-7-13 to 30-7-13 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60 3) TCLL: ASCE 7-16; Pr=30.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=40.0 psf; Pf=33.6 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat C; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.20 4) Unbalanced snow loads have been considered for this design. 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 33.6 psf on overhangs non-concurrent with other live loads. 6) Dead loads shown include weight of truss. Top chord dead load of 5.0 psf (or less) is not adequate for a shingle roof. Architect to verify adequacy of top chord dead load. 7) All plates are MT20 plates unless otherwise indicated. 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads. 9) Bearing at joint(s) 2, 10 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface. 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 764 lb uplift at joint 2 and 764 lb uplift at joint 10. 11) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer. 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.								
LOAD CASE(S) Standard								

Job 25080283B	Truss T30	Truss Type COMMON	Qty 2	Ply 1	1 Westwood C.C. 400733-012 Job Reference (optional)
UFP Site Built, LLC, UFP 20/20			Run: 8.830 s Apr 11 2025 Print: 8.830 s Apr 11 2025 MiTek Industries, Inc. Wed Aug 6 12:07:13 2025 Page 1 ID:ZHHB8ESp8faLeAkYUvv6z26yE-DRb6L8dXNxP1IIZFyWTTFJ2nS9i?NsIUYIR3Y?ygb?C		
0-10-8 0-10-8	8-6-0 8-6-0		15-0-0 6-6-0	21-6-0 6-6-0	30-0-0 8-6-0
					30-10-8 0-10-8

Scale = 1:51.9




Plate Offsets (X, Y)-- [2:0-1-10,Edge], [6:0-1-10,Edge], [8:0-1-8,0-1-8], [10:0-1-8,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 30.0	Plate Grip DOL 1.15	TC 0.98	Vert(LL) -0.33 in (loc) 10-13 >999 L/d 240	MT20	197/144
TCDL 5.0	Lumber DOL 1.15	BC 0.60	Vert(CT) -0.46 in (loc) 10-13 >779 180		
BCLL 0.0	Rep Stress Incr NO	WB 0.46	Horz(CT) 0.11 in 6 n/a n/a		
BCDL 5.0	Code IBC2021/TPI2014	Matrix-MS			Weight: 171 lb FT = 20%

#### LUMBER-

TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP 2400F 2.0E  
WEBS 2x4 SPF No.2

#### BRACING-

TOP CHORD 2-0-0 oc purlins (2-1-0 max.).  
BOT CHORD Rigid ceiling directly applied or 7-7-7 oc bracing.

**REACTIONS.** (lb/size) 2=2716/0-8-8, 6=2716/0-8-8  
Max Horz 2=-175(LC 15)  
Max Uplift 2=-765(LC 10), 6=-765(LC 11)

#### FORCES. (lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/32, 2-17=-6201/2085, 17-18=-6101/2088, 3-18=-5928/2104, 3-19=-5299/1831, 4-19=-5114/1853, 4-20=-5114/1853, 5-20=-5299/1830, 5-21=-5928/2104, 21-22=-6101/2088, 6-22=-6201/2085, 6-7=0/32  
BOT CHORD 2-10=-1819/5788, 9-10=-1117/3954, 8-9=-1117/3954, 6-8=-1819/5788  
WEBS 3-10=-1685/622, 4-10=-453/1798, 4-8=-454/1798, 5-8=-1685/622

#### NOTES


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=115mph (3-second gust) Vasd=91mph; TCDL=3.0psf; BCDL=3.0psf; h=20ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E)-0-7-13 to 3-4-3, Interior(1) 3-4-3 to 11-0-0, Exterior(2R) 11-0-0 to 19-0-0, Interior(1) 19-0-0 to 26-7-13, Exterior(2E) 26-7-13 to 30-7-13 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=30.0 psf (roof LL: Lum DOL=1.15; Plate DOL=1.15); Pg=40.0 psf; Pf=33.6 psf (Lum DOL = 1.15 Plate DOL = 1.15); ls=1.0; Rough Cat C; Partially Exp.; Ce=1.0; Cs=1.00; Cl=1.20
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 33.6 psf on overhangs non-concurrent with other live loads.
- 6) Dead loads shown include weight of truss. Top chord dead load of 5.0 psf (or less) is not adequate for a shingle roof. Architect to verify adequacy of top chord dead load.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 765 lb uplift at joint 2 and 765 lb uplift at joint 6.
- 9) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard







EAVE #1



GABLE #1



GABLE #2



EAVE #2

## Revisions:

8-6-2025: (HLK) #012 BLDG SIZE

BUILDING SIZE: 30x58x14'-4"

DATE: 1-20-2025  
James A. Koppenhaver, P.E.  
575 Van Reed Rd  
Wyomissing, PA 19610  
484-794-9949  
koppenhaverpe@gmail.com


DRAWN BY: HEIDI KLOCK


Job Number:

CHECKED BY: WESTWOOD-012

SHEET: Elevations

PPB. Inc.

Pioneer Pole Buildings, Inc.  
716 South Rt. 183  
Schuylkill Haven, PA 17972  
1-888-448-2505 Toll FreeJOB SITE ADDRESS:  
SAMECUSTOMER ADDRESS:  
WESTWOOD COUNTRY CLUB  
BRIAN STONE & DAVID McGREGOR  
800 MAPLE AVE E  
VIENNA, VA 22180  
703-755-5363 (H)  
954-260-2011 (M)



**(X) = DOWNSPOUT**

WINDOW & DOOR SCHEDULE			
SYM	TYPE OF WINDOW / DOOR	NOMIN.	R.O.
(1)	ENTRY DOOR 9-LITE	3068	38" x 82 1/2"
(2)	OVERHEAD DOOR	16X12	16'-0" x 12'-4"

8-6-2025: (HLK) #012 BLDG SIZ

BUILDING SIZE: 30x58x14'-4"

DATE:	1-20-2025
SHEET:	Pole Plan
James A. Koppenhaver, P.E. 575 Van Reed Rd Wyomissing, PA 19610 484-794-9949 koppenhaverpe@gmail.com	


## Revisions:


ALL RIGHTS RESERVED BY PIONEER POLE BUILDINGS, INC. NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION

**PPB. Inc**  
Pioneer Pole Buildings, Inc  
716 South Rt. 183  
Schuylkill Haven, PA 17972  
1-888-448-2505 Toll Free

JOB SITE ADDRESS  
SAME


CUSTOMER ADDRESS:  
WESTWOOD COUNTRY CLUB  
BRIAN STONE & DAVID McGREGOR  
800 MAPLE AVE E  
VIENNA, VA 22180  
703-755-5363 (H)  
954-260-2011 (M)






## TYP. CROSS SECTION


<b>Revisions:</b>	8-6-2025: (HLK) #012 BLDG SIZE		BUILDING SIZE: 30x58x14'-4"		DATE: 1-20-2025 SHEET: TYP Cross Section
	DRAWN BY: HEIDI KLOCK CHECKED BY: WESTWOOD-012		Job Number: <b>WESTWOOD-012</b>		
	<b>PPB. Inc.</b> Pioneer Pole Buildings, Inc. 716 South Rt. 183 Schuylkill Haven, PA 17972 1-888-448-2505 Toll Free	<b>JOB SITE ADDRESS:</b> SAME	<b>CUSTOMER ADDRESS:</b> WESTWOOD COUNTRY CLUB BRIAN STONE & DAVID McGREGOR 800 MAPLE AVE E VIENNA, VA 22180 703-755-5363 (H) 954-260-2011 (M)		
	ALL RIGHTS RESERVED BY PIONEER POLE BUILDINGS, INC. NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION				




FD 1 FOOTER DETAIL




OD 1 O.H. DOOR HEADER DETAIL





OD 2 O.H. DOOR JAMB DETAIL



RE 1 STEEL ROOF EDGE DETAIL



GD 2 FLUSH GABLE DETAIL

CONTINUOUS SPLICED  
2X10 MSR OR BETTER  
HEADER ATTACHMENT

SR 1 STEEL ROOF RIDGE DETAIL

## Revisions:

8-6-2025: (HLK) #012 BLDG SIZE


BUILDING SIZE: 30x58x14'-4"








DATE: 1-20-2025


James A. Koppenhaver, P.E.  
575 Van Reed Rd  
Wyomissing, PA 19610  
484-794-9949  
koppenhaverpe@gmail.comDRAWN BY: HEIDI KLOCK  
CHECKED BY: WESTWOOD-012

SHEET: Detail A


PPB. Inc.

Pioneer Pole Buildings, Inc.  
716 South Rt. 183  
Schuylkill Haven, PA 17972  
1-888-448-2505 Toll FreeJOB SITE ADDRESS:  
SAMECUSTOMER ADDRESS:  
WESTWOOD COUNTRY CLUB  
BRIAN STONE & DAVID McGREGOR  
800 MAPLE AVE E  
VIENNA, VA 22180  
703-755-5363 (H)  
954-260-2011 (M)





BB 1 BEAM BRACKET DETAIL



TBC 1 TRUSS TO BEAM CONNECTION

Revisions:	8-6-2025: (HLK) #012 BLDG SIZE	BUILDING SIZE: 30x58x14'-4"	DATE: 1-20-2025	James A. Koppenhaver, P.E. 575 Van Reed Rd Wyomissing, PA 19610 484-794-9949 koppenhaverpe@gmail.com
	DRAWN BY: HEIDI KLOCK CHECKED BY: WESTWOOD-012	Job Number: WESTWOOD-012	SHEET: Detail C	
	PPB. Inc. Pioneer Pole Buildings, Inc. 716 South Rt. 183 Schuylkill Haven, PA 17972 1-888-448-2505 Toll Free	JOB SITE ADDRESS: SAME	CUSTOMER ADDRESS: WESTWOOD COUNTRY CLUB BRIAN STONE & DAVID McGREGOR 800 MAPLE AVE E VIENNA, VA 22180 703-755-5363 (H) 954-260-2011 (M)	
	ALL RIGHTS RESERVED BY PIONEER POLE BUILDINGS, INC. NOT TO BE COPIED OR REPRODUCED WITHOUT WRITTEN PERMISSION			

