




MIMIK 20 M TYPE IV




Part number	071631
Lampholder:	LED
Wattage:	15 W
Finish:	AN-96 / Iron gray / Textured
Degree of protection:	IP65
CRI:	70
Kelvin:	3000
Luminaire lumen output:	1319 lm
L:	L80
B:	B10
Lifetime:	60000 h
cULus:	✓
Voltage:	120-277 V




Description

- Wall- and post- mount series. Fixtures consist of:
- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
 - Copper-free precision die-cast aluminum housing and mounting plate.
 - Extra-clear, flat, tempered silk-screened soda-lime glass diffuser.
 - Custom molded, anti-aging gasket(s).
 - Stainless steel external hardware.
 - Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
 - High-transmittance transparent optics.
 - IESNA Type IV light distribution.
 - Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
 - Optional, integral, emergency battery-pack designed for a minimum operation of 90 minutes (EMPK versions).
 - Customizing facade faceplate available for MIMIK FLAT versions (ordered separately).
 - Post accessory available for MIMIK 20 (ordered separately).
 - Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
 - Optional clear plexiglass panel can be customized with logos for signage or wayfinding (LINE BOLLARD). Consult factory for more information.
 - Product meets Buy American Act requirements within ARRA.
 - 5-year warranty.

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

MIMIK 20 BOLLARD




02401
Bollard h 40"
Iron gray

MIMIK 20 LINE BOLLARD



02404
Line Bollard h 40"
Iron gray

MIMIK 20



310445
Customising ring / Facade Accessory
Iron gray