



Plan View
Scale - 1" = 14ft

Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage
○	R	14	EATON - PORTFOLIO (FORMER COOPER LIGHTING)	LDSQ4B20D010 EU4B10208035 4LBSQ1LI	PORTFOLIO LD4 SERIES 4" RECESSED FIXTURE WITH A SQUARE LOW IRIDESCENT TRIM. MEDIUM DISTRIBUTION WITH SPECULAR CLEAR TRIM WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W DL3-21.8 6 W DLE-22.46 W	HIGH LUMEN LED 3500 K ABSOLUTE PHOTOMETRY IS BASED ON CALIBRATION FACTORS CREATED USING LAB LUMEN STANDARDS IN GONIOPHOTOMETER WITH TEST DISTANCE OF 28.75 FEET	1	Type R.ies	1965	0.85	20.8
□	S3	1	SELUX Corporation	SAC2L-R3-X-LG4500-30-XX-XX-UNV	n/a	n/a	1	Type S3.IES	3877	0.85	49.87
○	S3C	12	SELUX Corporation	SAC2L-R3-X-5G450-30-XX-XX-UNV-HS	Formed gray aluminum housing, clear optics with house shie lds, patterned enclosure	Seven white LEDs	1	Type S3C.ies	3501	0.85	39
□	S5	1	SELUX Corporation	SAC2L-R5-X-LG4500-30-XX-XX-UNV	n/a	n/a	1	Type S5.IES	4044	0.85	49.81
—	X	14	Lithonia Lighting	KBR8 LED 16C 450 AMBLW SYM MVOLT	KBR8 WITH 4 LIGHT BOARDS (16 LEDs), 450mA DRIVER, LW AMBER COLOR TEMP, AND SYMMETRIC OPTIC		1	Type X.ies	374	1	20
○	R1	6	EATON - PORTFOLIO (FORMER COOPER LIGHTING)	LDSQ4B10D010 EU4B10208035 4LBSQ1LI	PORTFOLIO LD4 SERIES 4" RECESSED FIXTURE WITH A SQUARE LOW IRIDESCENT TRIM. MEDIUM DISTRIBUTION WITH SPECULAR CLEAR TRIM WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W DL3-11.1 W DLE-11.39 W	HIGH LUMEN LED 3500 K ABSOLUTE PHOTOMETRY IS BASED ON CALIBRATION FACTORS CREATED USING LAB LUMEN STANDARDS IN GONIOPHOTOMETER WITH TEST DISTANCE OF 28.75 FEET	1	Type R1.ies	1041	1	10.05
□	R2	10	EATON - PORTFOLIO (FORMER COOPER LIGHTING)	LDSQ4B10D010 EU4B10208035 4LBSQWWLI	PORTFOLIO 4 INCH SQUARE SINGLE WALLWASH RECESSED DOWNLIGHT, WITH SPECULAR CLEAR TRIM	(1) HIGH LUMEN LED 80CRI / 3500K CCT ABSOLUTE PHOTOMETRY IS BASED ON CALIBRATION FACTORS CREATED USING LAB LUMEN STANDARDS IN GONIOPHOTOMETER WITH TEST DISTANCE OF 28.75 FEET	1	Type R2.ies	858	1	10.05
—	T	43	Luminii	KBM-F-H-41K-XX-XX-48	Kurba Horizontal	2835 LED	1	Type T.IES	487	0.7	13.3
—	U	9	COOPER LIGHTING SOLUTIONS - IO LED (FORMERLY EATON)	LM-05L-930-120-UNV-S-STD-2F	CoviO LED ARCHITECTURAL COVE LUMINAIRE. 500 LUMENS PER FOOT, 24 INCH FIXTURE.	(90) 3000K CCT, 90 CRI LEDS	90	Type U.ies	13	0.7	9.9

Statistics						
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Full Site Plan	+	1.145 fc	103.328 fc	0.000 fc	N/A	N/A
Police Parking	■	1.472 fc	7.272 fc	0.008 fc	909.0:1	184.0:1
Public Entryway	×	2.008 fc	8.288 fc	0.074 fc	112.0:1	27.1:1
Public Parking	✗	1.105 fc	5.406 fc	0.012 fc	450.5:1	92.1:1

Designer
Patrick Hishta
Date
5/5/2020
Scale
Not to Scale
Drawing No.
Summary