
## Section 18-219 Residential - Single-Unit, 10,000 sq. ft. Zone (RS-10)

## 1. RS-10 Purpose



Principal Structure Count: 1 per lot max.

Principal Structure Count: 1 per lot max.					
BUILDABLE LOT DIMENSIONS					
	Lot A	rea Per Dwelling	Unit	10,000 sq. ft. min.	
FW	Lot W	idth at Front Lot	Line	45 ft. min.	
BW	Lot W	idth at Front Bui	lding Line	60 ft. min.	
MW	Lot W	idth at Midline		75 ft. min.	
RESIDENTIAL COVERAGE					
Lot coverage		25% max.			
Outd		5% max. covered by decks			
living cove			q. ft. of decks may be covered, ions outlined in §18-213		
BUILDING STANDARDS					
Н	Buil	ding Height	35 ft. max	•	

DOILDING FLACEMENT STANDARDS				
FY	Front Yard Setback	25 ft. min. from front property line, incl. after any required dedication		
ISY	Interior Side Yard Setback	12 ft. min. Non-Residential Principal Structures: 30 ft. min.		
CSY	Corner Side Yard Setback	25 ft. min.		
RY	Rear Yard Setback	35 ft. min.		

BUILDING PLACEMENT STANDARDS

## **Reference to Other Standards**

- » Uses and Use Standards: See Article 3;
- » Accessory structure setbacks: See Article 4A
- » Development Standards Single-Unit Detached Residential Uses: See Article 4A;
- » Development Standards Public, Institutional, and Community Uses See Article 5B

Zoning and Subdivision Ordinance

**EFFECTIVE 01 JANUARY 2024**