

V2 ECO3S LW2 SS 1.0W POWER BY SAMSUNG LED

Operating Power : DC 12V
 Power Dissipation : 1.0W
 Dimensions : 2.6L x 0.6W x 0.4H inch

Viewing Angle : 140°
 Waterproofing Rate : IP68
 Module/ft : 2 Modules



Color Temp.

ECO3S-LW2-SS 3000K, 86 lm 2.0W 1.0W 93 lm 51 Modules

FEATURES

- NC LED's most cost-efficient model
- 140 degree angle lens that spreads light evenly for no hot spots
- Ensures excellent transmittance and uniform lighting
- Specially designed durable polycarbonate cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 93 lm/W
- Easy installation with double sided 3M tape and screw holes for extra security
- IP68 Waterproof
- Approved by UL, CE, RoHS / LED provided by Samsung

V2 ECO3S LW



Operating Power : DC 12V
 Power Dissipation : 0.72W / 1.0W
 Dimensions : 2.6L x 0.6W x 0.4H inch

Viewing Angle : 140°
 Waterproofing Rate : IP68
 Module/ft : 2 Modules



ECO3S-LW2-NS-0.72W 3000K, 100 lm 1.44W 0.72W 90 lm 71 Modules

FEATURES

- NC LED's most cost-efficient model
- 140 degree angle lens that spreads light evenly for no hot spots
- Ensures excellent transmittance and uniform lighting
- Specially designed durable polycarbonate cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 90 lm/W
- Easy installation with double sided 3M tape and screw holes for extra security
- IP68 Waterproof
- Approved by UL, CE, RoHS

New Jersey

NES Light INC.
 1179 Edgewater Ave. Ridgefield, NJ 07657
 Tel : (201) 840-0400
 E-mail : neslight@gmail.com
 info@neslight.com