


MIMIK 50 M TYPE IV



Part number	079911
Lampholder:	LED
Wattage:	53 W
Finish:	GR-94 / Aluminum metallic / Textured
Degree of protection:	IP65
CRI:	80
Kelvin:	3000
Luminaire lumen output:	5520 lm
L:	L80
B:	B10
Lifetime:	71000 h
cULus:	✓




Description

Wall mount series. Fixtures consist of:

- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing and mounting plate.
- Extra-clear, flat, tempered silk-screened soda-lime glass diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- High-transmittance transparent optics.
- Single (M) or dual (B) light emission.
- IESNA Type IV light distribution.
- Standard dual-circuit wiring and dimming for dual (B) light emission models.
- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- BUTTON and SWIVEL 120-277 V (50 / 60 Hz) photoelectric switch options available (ordered separately).
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.

Photometric data



Technical drawings

